




主要技术参数 (重合器用) MAIN TECHNICAL DATA (FOR RECLOSER)	
额定电压 Rated voltage	38KV
额定电流 Rated current	630A
额定频率 Rated frequency	50/60HZ
额定短时(1min)工频耐受电压Rated Short-time(1min) power-frequency withstand voltage	*70KV
额定雷电冲击耐受电压(峰值)Rated Lightning impulse withstand voltage(peak)	*170KV
额定短路开断电流 Rated short-circuit breaking current	12.5KA
额定短路开断电流开断次数Operations of short-circuit breaking current interruption	15-20%,88/45-55%,112/90-100%,32
额定短路关合电流 Rated short-circuit making current	31.5KA
额定峰值耐受电流 Rated peak withstand current	31.5KA
额定短时耐受电流(3秒) Rated short-time withstand current(3s)	12.5KA
额定单个电容器组开断电流 Rated breaking current of single capacitor bank	#630A
额定背对背电容器开断电流 Rated breaking current of back to back capacitor bank	#400A
额定瞬时电流Rated momentary current,RMS asymmetrical	25.6KA
额定电缆充电开断电流 Rated cable-charging breaking current	25KA
额定空载变压器开断电流 Rated breaking current of no-load transformer	22KA
额定触头压力下限时的回路电阻 Circuit resistance at minimum added force	≤25 μ Ω
机械寿命 Mechanical life	10000次
触头自闭力 Closing force due to bellows and atmosphere	80 ± 30N
额定开距下的触头反力 Force required to hold contacts open at full stroke	160 ± 30N
触头允许磨损厚度 Contact erosion limit	3mm
贮存期 Shelf life	20年
动触头导向套耐受温度 Temperature endurance of lead bushing of moving	170℃
额定操作顺序 Rated operating sequence	0-0.3s-CO-2s-CO-2s-CO
配套真空开关的机械参数(建议值)MECHANICAL DATA OF CIRCUIT-BREAKING RECOMMENDATIONS WITH THE INTERRUPTERS	
触头开距 Rated contact stroke	14 ± 0.5mm
触头接触行程 Contact connection stroke	4 ± 1mm
平均分闸速度 (0-6mm行程) Average opening speed (0-6mm stroke)	1.6 ± 0.2m/s
平均合闸速度 (6mm-触头闭合) Average closing speed (6mm-contact making)	0.8 ± 0.2m/s
额定触头压力 Added force on closed contacts	1200 ± 200N
触头合闸弹跳时间 Max.bouncing duration	≤3ms
触头分合闸不同期 Out of simultaneity of contact closing and opening	≤2ms
分闸触头反弹幅值 Max. rebound distance	≤1mm
备注 (Note):	
# 订货时需与BOV公司协商(Must consult with BOV);	
* 须有外绝缘保护 (With insulation cover);	

