



主要技术参数（ 接地开关用 ） MAIN TECHNICA DATA (FOR EARTHING SWITCH)	
额定电压 Rated voltage	12KV
额定电流 Rated current	630A
额定频率 Rated frequency	50HZ
短时(1min)工频耐受电压 Short-time(1min) power-frequency withstand voltage	*42KV
雷电冲击耐受电压(峰值) Lightning impulse withstand voltage(peak)	*75KV
额定峰值耐受电流 Rated peak withstand current	50KA
额定短时耐受电流(4秒) Rated short-time withstand current(4s)	20KA
额定触头压力下限时的回路电阻 Circuit resistance at minimum added force	≤40 μ Ω
机械寿命 Mechanical life	10000次
触头自闭力 Closing force due to bellows and atmosphere	40 ± 20N
额定开距下的触头反力 Force required to hold contacts open at full stroke	110 ± 20N
贮存期 Shelf life	20年
质量/动触头质量 Total mass of interrupter/Moving mass of interrupter	0.70Kg/0.21Kg
配套真空开关的机械参数(建议值)MECHANICAL DATA OF CIRCUIT-BREAKING RECOMMENDATIONS WITH THE INTERRUPTER	
触头开距 Rated contact stroke	7 ± 1mm
触头接触行程 Contact connection stroke	4 ± 1mm
额定触头压力 Added force on closed contacts	700 ± 50N
备注（ Note ）： * 须有外绝缘保护（ With insulation cover ）；	